

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number
WO 2004/009897 A1

(51) International Patent Classification⁷: D06B 23/14
(21) International Application Number: PCT/NL2003/000512
(22) International Filing Date: 11 July 2003 (11.07.2003)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data: 1021142 24 July 2002 (24.07.2002) NL
(71) Applicant (for all designated States except US): STORK PRINTS B.V. [NL/NL]; 1-3 Raamstraat, NL-5831 AT Boxmeer (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(72) Inventor; and
(75) Inventor/Applicant (for US only): VAN SCHEPDAEL, Ludo, Jean, Maria, Mathilde [BE/BE]; Tweebruggenstraat 45, B-3020 Herent (BE).
(74) Agent: RIEMENS, R., H.; Exter Polak & Charlouis B.V., P.O. Box 3241, NL-2280 GE Rijswijk (NL).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE AND METHOD FOR THE PIECE-WISE OR BATCH-WISE REFINING OF PIECES OF A SUBSTRATE, IN PARTICULAR A TEXTILE SUBSTRATE, UNDER HIGH PRESSURE



(57) Abstract: Device for the piece-wise or batch-wise refining of pieces of a substrate, in particular a textile substrate, under high pressure with a treatment medium, comprising: a substantially cylindrical pressure vessel (1), which is provided with a closable feed aperture (4) for placing the pieces of substrate in the pressure vessel (1); a pipe system (7) for feeding a treatment medium to and discharging it from the pressure vessel (1) under high pressure during treatment. The cylindrical pressure vessel is provided on at least one of the two end faces with an aperture that is closable by a lid (2, 3), which aperture forms the feed aperture (4). The device comprises retaining means for keeping the lid (2, 3) in place in a sealing manner during treatment, and the retaining means comprise a bounding frame (10) that is circumferentially closed, with two interconnected end pieces (11, 12) situated at a distance from each other, which end pieces in a closed position can be slid over the pressure vessel (1) and thereby retain the end faces of the pressure vessel (1) in the axial direction.

WO 2004/009897 A1

THIS PAGE BLANK (USPTO)

Short title: Device and method for the piece-wise or batch-wise refining of pieces of a substrate, in particular a textile substrate, under high pressure.

5

The invention relates to a device for the piece-wise or batch-wise refining of pieces of a substrate, for instance a textile substrate, under high pressure with a treatment medium according to the preamble of claim 1.

Such a device is known, for example from EP-1.152.081-A1, which discloses a device for dyeing a textile substrate. The device comprises a dye vessel, in which a textile substrate can be placed at the beginning of each cycle. To this end, the dye vessel is provided with a feed aperture that is to be closed by a cover element. The dye vessel forms part of a main pipe system, in which a fluid containing dyestuff is circulated under high pressure. The pressure applied during the dyeing operation is at least so high that at the desired treatment temperature the fluid is in a supercritical or near critical state. Normally, the pressure lies in the range of $5 \times 10^6 - 5 \times 10^7$ pascal (50-500 bar).

A disadvantage in the case of this known device is that the dye vessel has to be of a heavy construction, in order to be able to withstand the high working pressures. This makes the device expensive to manufacture. It has to be possible to open the cover element and close it again after each treatment cycle. Very heavy closing means, such as large bolts and nuts, are needed in order to be able to keep the cover element in place in a sealing manner at the high working pressures. The cover element itself also has to be of a very thick-walled and heavy construction. The lid in this case generally rests with an axial sealing ring against a flange of the pressure vessel. In order to be able to make the axial seal secure, the retaining means must be brought under high tension. This is usually a time-consuming and difficult operation, as is removing of the closing means again after the treatment cycle has been completed.

The object of the present invention is to at least partially overcome the abovementioned disadvantages, or to provide a usable alternative. In particular, the object of the invention is to

provide a treatment device of the abovementioned type that is cheap to manufacture and is characterized by a relatively low weight.

This object is achieved according to the present invention by a device according to claim 1. In this case a bounding frame that is closed around its circumference is provided with two interconnected end pieces situated at a distance from each other. The bounding frame and the pressure vessel can be slid into each other, in which case the end faces of the pressure vessel are retained in the axial direction by the two end pieces of the bounding frame. Owing to the fact that a feed aperture that can be closed by a lid is provided on at least one of the two end faces of the pressure vessel, the lid is advantageously retained directly by the bounding frame in the axial direction. The axial pressure forces acting upon the lid are advantageously dissipated by the bounding frame, and therefore do not act upon the cylinder wall of the pressure vessel. The cylinder wall therefore only has to withstand the radial pressure forces acting upon it. As a result of this separation of axial and radial forces, the design of the pressure vessel walls becomes simpler. For example, in the case of vessel walls of composite materials, glass windings or carbon fibre windings over the end faces of the pressure vessel or with an axial component can be dispensed with, owing to the fact that only tangential cylinder wall windings are needed. A vessel having walls of composite materials has the advantage that the vessel can be given a better thermic isolation and a lower thermic inertia, which leads to a shorter cycle time, improved steering and control, and energy saving of the refining process.

During a treatment cycle a seal between the lid and the pressure vessel can remain very reliably secured. During the treatment cycle the bounding frame is placed under tensile stress substantially only in the axial direction. The bounding frame that is closed on all sides can consequently advantageously be of a relatively lightweight construction and, for example, comprise lightweight wound fibres. Owing to the fact that it is now possible to have the lid supported over a large part of its outer surface, the lid can also be of a relatively lightweight design. Sliding the pressure vessel and the bounding frame in or out of each other at the beginning and end of a treatment cycle is a simple operation, which can easily be automated. It has been found that the device according to the invention can be manufactured considerably more

cheaply than is the case according to the prior art. For example, the costs of the assembly of pressure vessel, lid and bounding frame can be a factor of two to three times lower than for the assembly of pressure vessel, lid and retaining means according to the prior art.

5 Considerable reductions in weight can also be achieved.

The device is intended for the piece-wise refining of pieces of a substrate under high pressure with a treatment medium. Refining in the context of the invention should be understood as meaning, inter alia, dyeing, washing, cleaning, de-greasing, or otherwise treating
10 or pre-heating a substrate. The treatment medium is preferably formed by supercritical or near critical fluid, for example carbon dioxide, containing for example solid dye particles or cleaning particles.

In a particular embodiment the lid comprises a cylindrical wall part, which is intended to be placed in the cylindrical
15 circumferential wall of the pressure vessel. At least one sealing ring is provided between this cylindrical wall part and an inner circumferential wall of the pressure vessel. The sealing ring in this case is designed to permit a slide of the lid in the axial
20 direction relative to the pressure vessel. This advantageously means that a certain elongation of the bounding frame in the axial direction can be compensated for by a corresponding axial movement of the lid relative to the inner circumferential wall of the pressure vessel.

25 Further preferred embodiments of the invention are described in the subclaims.

The invention also relates to a method for the piece-wise or batch-wise refining of pieces of a substrate, for instance a textile substrate, under high pressure with a treatment medium according to
30 claims 13-15, and to the use of a device according to claim 16.

The invention will be explained in greater detail with reference to the appended drawing, in which:

Figure 1 is a diagrammatic view in perspective of an embodiment of the device according to the invention, with the bounding frame
35 placed in a closed position;

Figure 2 is a view according to Figure 1, with a lowered bounding frame;

Figure 3 is a more detailed view in perspective of Figure 1;

Figure 4 is a view in longitudinal section of the right end

face in Figure 3; and

Figure 5 is a view on an enlarged scale of the lid with pipe system from Figure 4 opening into it.

5 The pressure vessel is indicated in its entirety by 1 in Figures 1 - 5. The pressure vessel 1 is of a cylindrical design and comprises a feed aperture 4 closable by a lid 2, 3 on both end faces. The pressure vessel 1 rests on two stands 5. Inside the pressure vessel 1 is a treatment chamber, in which one or more pieces of textile substrate is (are) to be placed at the beginning
10 of a treatment cycle.

A pipe system 7, which opens into the pressure vessel 1, is provided. The pipe system 7 is intended for connection to feed means for feeding in and discharging a treatment medium, in particular supercritical or near critical fluid, under high pressure.

15 In order to be able to maintain a high pressure inside the pressure vessel 1 during the treatment, a bounding frame 10, comprising two interconnected end pieces 11, 12 situated at a distance from each other, is provided. The bounding frame 10 is closed allround and can be pushed over the pressure vessel 1. This
20 is the closed position shown in Figures 1 and 3, in which the two lids 2, 3 on the end faces of the pressure vessel 1 are retained in the axial direction by the bounding frame 10, and in particular by its end pieces 11, 12. In this way the axial pressure forces acting upon the lids 2, 3 are dissipated over the bounding frame, away from
25 the cylindrical wall of the pressure vessel 1, and cancel each other out.

At the beginning or the end of a treatment cycle the bounding frame 10 can simply be slid downwards over the stands 5, as a result of which the lids 2 and/or 3 can be opened (see Figure 2).

30 As can be seen clearly in Figures 4 and 5, the lid 3 comprises a cylindrical wall part 15, which in the closed position extends in the axial direction along an inner circumferential wall 16 of the pressure vessel 1. The cylindrical wall part 15 is provided with a circumferential groove, in which a sealing ring 17 is accommodated.
35 The cylindrical wall part 15 with the sealing ring 17 can slide slightly in the axial direction of the pressure vessel 1 along the inner circumferential wall 16, without a leak occurring in the process. This axial movement facility makes it possible to absorb axial elongation of the bounding frame, which can occur during a

treatment cycle. Elongation in the bounding frame occurs through the fact that the lids are pressed very forcefully against the end pieces of the bounding frame, under the influence of the high pressure in the pressure vessel. The elongation and the axial movement of the lids 2, 3 in this case are partly a function of the length of the pressure vessel 1 and the bounding frame 10 respectively. Through the axial freedom of the lids 2, 3, the cylindrical wall of the pressure vessel 1 remains free from axial load.

The lids 2, 3 are provided with a holding part, which is, for example, formed by a flange 19 extending outside the pressure vessel 1. The holding part is intended to permit removal of the cylindrical wall part 15 in the axial direction from the pressure vessel 1 if the bounding frame 10 is slid away.

In the embodiment illustrated the bounding frame 10 is composed of two arch-shaped parts 20, 21 and two straight parts 22, 23. This means that bending moments in the bounding frame 10 are prevented, with the result that the weight can be lower. Two substantially semi-cylindrical retaining pieces 25, 26, which can be connected to the arch-shaped parts 20, 21 respectively, and in the closed position rest against the lids 2, 3, are further advantageously provided.

The semi-cylindrical retaining pieces 25, 26 are formed here by aluminium or steel plates placed at a distance from each other. This has proved to give sufficient strength and saves weight. In a variant the retaining pieces are of a solid design and/or are made of a different material. It is also possible to use composite plates, which are either glued directly to each other or connected to each other with foam sheets between them.

The pipe system 7 opens into the lid 3. The feed pipe here is enclosed by the discharge pipe. In order to permit sliding of the bounding frame 10 over the pressure vessel 1, a slotted opening 30 is provided in the frame 10, and in particular in the corresponding retaining piece 26.

The lids 2, 3 in the closed position are supported over a large part of their outer surface against the bounding frame 10. This means that the lids 2, 3 can advantageously be made of a relatively thin-walled design, or of a relatively weak material. The thickness of the lid can in this case, for example, be made equal to the

unsupported width of the lid. The cylindrical wall part 15 of the lid is, for example, of a partially hollow design. The lid can be made of, for example, stainless steel or a composite material.

The bounding frame 10 can, for example, be made of steel, for example of steel plates or wound steel strips. Further weight reduction can be achieved by making the bounding frame 10 of composite material, in particular of fibre-reinforced material. More particularly, the bounding frame 10 is made of wound fibre-reinforced material, for example of plastic reinforced with wound glassfibre or carbon fibre. The fibres in this case extend substantially in the circumferential direction of the bounding frame 10.

The cylindrical circumferential wall of the pressure vessel 1 is preferably made of a composite material that on the inside is coated with a layer of material, for example stainless steel, which is resistant to the effect of the treatment medium used. The composite in this case comprises in particular unidirectionally circumferentially wound fibres.

The device is preferably used for dyeing pieces of textile substrate with a fluid under high pressure that contains dye particles. In this case the pipe system 7 is connected to feed means for feeding in this fluid containing dye particles. The fluid in this case is advantageously brought to a supercritical or near critical state, in which the dye particles are dissolved. The supercritical or near critical fluid used can be, inter alia, CO₂, N₂O, lower alkanes and mixtures of the above. Examples of lower alkanes are ethane and propane. The dyeing conditions of the dyeing process according to the invention are selected on the basis of the textile substrate to be dyed and also the dyestuff used. In general, the temperature lies in the range 20 - 220°C, preferably 90 - 150°C. The pressure applied during the dyeing operation must be at least so high that the fluid is in the supercritical or near critical state at the prevailing temperature. The pressure usually lies in the range 5×10^6 - 5×10^7 pascal (50 - 500 bar), more particularly between 2×10^7 - 3×10^7 pascal (200 and 300 bar). As heating system, a heat exchanger can be accommodated in the pipe system 7.

The method for refining a substrate with the device shown is, for example, as follows.

Pieces of textile substrate are placed in the pressure vessel 1

by way of the feed aperture 4. The lids 2 and 3 are subsequently put on, and the pressure vessel 1 and the bounding frame 10 are slid into each other. The lids 2, 3 are now retained in the axial direction, and the pressure vessel 1 can, by way of the pipe system 5 7, be placed and held under high pressure for a desired cycle time of, for example, several hours by feeding in treatment medium under high pressure. On completion of the cycle time, the bounding frame 10 is lowered, and lid 2 or 3 removed, after which the treated product can be removed from the pressure vessel 1.

10 Many variants are possible, apart from the embodiment illustrated. For instance, the pressure vessel and bounding frame can be set up either vertically or horizontally. Instead of moving the bounding frame, the pressure vessel can also be removed from it. The mutual direction of movement can be either horizontal or 15 vertical. The feed and discharge pipes of the pipe system can also be connected individually to the lids, or can open into the pressure vessel at another point. The bounding frame and/or the lid can be of a different shape, in which case the surfaces resting against each other can be given, for example, a profiled shape, so long as this 20 does not stand in the way of said surfaces being capable of sliding relative to each other.

In addition to the application of dyeing pieces of a textile substrate, the device can also advantageously be used for treating other kinds of substrate or for refining a substrate in another way, 25 for example washing the substrate. Examples of articles that can suitably be refined with the device and method of the invention include fabrics such as woven and non-woven fabrics formed from materials such as cotton, wool, silk, leather, rayon, polyester, acetate, fiberglass, furs, etc. These fabrics may have been formed 30 into items such as clothing, work gloves, rags, leather goods (e.g. handbags and brief cases), etc. The present device and method may also be used to refine, in particular wash, clean or degrease, non-fabric articles such as semiconductors, micro electromechanical devices, opto electronics, fiber optics, and machined or fabricated 35 metal parts. Furthermore food stuffs and polluted ground may be treated with the device and method according to the present invention..

According to the invention, a user-friendly, efficiently working device is therefore provided, which device can be of a

lightweight construction, and in particular has proved to be extremely reliable as regards the sealing effect during refining treatments of pieces of textile substrate under very high pressure.

CLAIMS

1. Device for the piece-wise or batch-wise refining of pieces of a substrate with a treatment medium under high pressure, comprising:

- 5 - a substantially cylindrical pressure vessel (1), which is provided with a closable feed aperture (4) for placing the pieces of substrate in the pressure vessel (1);
- a pipe system (7) for feeding the treatment medium to and discharging it from the pressure vessel (1) under high pressure
10 during treatment;

characterized in that

the cylindrical pressure vessel is provided on at least one of the two end faces with an aperture that can be closed by a lid (2, 3), which aperture forms the feed aperture (4),

- 15 in that the device comprises retaining means for keeping the lid (2, 3) in place in a sealing manner during treatment,

and in that the retaining means comprise a bounding frame (10) that is circumferentially closed, with two interconnected end pieces (11, 12) situated at a distance from each other, which end pieces in
20 a closed position can be slid over the pressure vessel (1) and thereby retain the end faces of the pressure vessel (1) in the axial direction.

2. Device according to claim 1, in which the lid (2, 3) comprises
25 a cylindrical wall part (15) that in a position closing the feed aperture (4) extends in the axial direction along an inner circumferential wall (16) of the pressure vessel (1),

in which at least one sealing ring (17) is provided between said cylindrical wall part (15) and the inner circumferential wall
30 (16) of the pressure vessel (1), and

in which the sealing ring (17) permits a slide of the lid (2, 3) in the axial direction relative to the inner circumferential wall (16) of the pressure vessel (1).

- 35 3. Device according to claim 1 or 2, in which the lid (2, 3) is provided with a holding part, for the purpose of removing the cylindrical wall part (15) from the pressure vessel (1) in the axial direction.

4. Device according to one of the preceding claims, in which the

bounding frame (10) comprises two straight and two arch-shaped parts.

5 5. Device according to claim 4, in which two substantially semi-cylindrical retaining pieces, which in the closed position lie between the arch-shaped parts of the bounding frame (10) and the end faces of the pressure vessel (1), are provided.

10 6. Device according to one of the preceding claims, in which the pipe system (7) opens into the lid (2, 3).

15 7. Device according to claim 6, in which a slotted opening (30) is provided in the bounding frame (10), for the accommodation in a sliding manner in said opening of the part of the pipe system (7) opening into the lid (2, 3).

20 8. Device according to one of the preceding claims, in which the two end faces of the pressure vessel (1) are provided with feed apertures (4) that are closable by lids (2, 3).

25 9. Device according to one of the preceding claims, in which the bounding frame (10) is made of composite material, in particular of fibre-reinforced material.

30 10. Device according to claim 9, in which the bounding frame (10) is made of wound fibre-reinforced material, in particular of wound glassfibre-reinforced plastic.

35 11. Device according to one of the preceding claims, in which the pipe system (7) connects to feed means for feeding in supercritical or near critical fluid.

12. Device for the piece-wise or batch-wise refining of pieces of textile substrate, according to one of the preceding claims.

13. Method for the piece-wise or batch-wise refining of pieces of a substrate with a treatment medium under high pressure with a device according to one of the preceding claims, comprising the following steps:

- placing one or more pieces of the substrate in the pressure vessel (1);
- closing the feed aperture by putting on the lid (2, 3);
- sliding the pressure vessel and the bounding frame (10) into each other;
- feeding the treatment medium to the pressure vessel (1) at high pressure for a desired cycle time;
- after completion of the cycle time sliding the pressure vessel and the bounding frame (10) out of each other and opening the lid (2, 3); and
- removing the refined substrate from the pressure vessel (1).

14. Method for the piece-wise or batch-wise refining of pieces of a textile substrate according to claim 13, comprising the step:

- placing one or more pieces of the textile substrate in the pressure vessel (1).

15. Method according to claim 13 or 14, in which the treatment medium comprises CO₂, N₂O, lower alkanes such as ethane and propane and mixtures thereof, in particular in a near critical or supercritical state.

16. Use of a device according to one of claims 1-12, for the piece-wise or batch-wise refining of pieces of textile substrate.

THIS PAGE BLANK (USPTO)




Fig. 1




Fig. 2

DT01 Rec'd PCT/PTC 20 JUL 2005

THIS PAGE BLANK (USPTO)




Fig. 3

THIS PAGE BLANK (USPTO)




Fig. 4




Fig. 5

DT01 Rec'd PCT/PTC 20 2005

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International application No
PCT/IL 03/00512

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 D06B23/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 D06B F16J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 1 435 592 A (HAWKER SIDDELEY DYNAMICS LTD) 27 June 1966 (1966-06-27) page 1, left-hand column, line 1 -right-hand column, line 14; figures 1-3 ----	1, 12, 13, 16
A	DE 35 24 415 A (SANDO IRON WORKS CO) 16 January 1986 (1986-01-16) ----	
A	US 4 944 923 A (HEINRICHS HARTMUT ET AL) 31 July 1990 (1990-07-31) -----	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the International filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

15 October 2003

Date of mailing of the international search report

23/10/2003

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van Gelder, P

INTERNATIONAL SEARCH REPORT

International application No
PCT/ 3/00512

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
FR 1435592	A	27-06-1966	NONE		
DE 3524415	A	16-01-1986	DE	3524415 A1	16-01-1986
US 4944923	A	31-07-1990	DE	3620381 A1	14-01-1988

INTERNATIONAL SEARCH REPORT

Application No
PCT/NL 03/00512

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 D06B23/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 D06B F16J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 1 435 592 A (HAWKER SIDDELEY DYNAMICS LTD) 27 June 1966 (1966-06-27) page 1, left-hand column, line 1 -right-hand column, line 14; figures 1-3 ----	1, 12, 13, 16
A	DE 35 24 415 A (SANDO IRON WORKS CO) 16 January 1986 (1986-01-16) ----	
A	US 4 944 923 A (HEINRICHS HARTMUT ET AL) 31 July 1990 (1990-07-31) -----	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

15 October 2003

Date of mailing of the international search report

23/10/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van Gelder, P

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International application No
PCT/NL 03/00512

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 1435592	A	27-06-1966	NONE	
DE 3524415	A	16-01-1986	DE 3524415 A1	16-01-1986
US 4944923	A	31-07-1990	DE 3620381 A1	14-01-1988

THIS PAGE BLANK (USPTO)